



Document Solutions

> PRINT > COPY > SCAN > FAX

**TASKalfa 5003i**  
**TASKalfa 6003i**

MONOCHROME MULTIFUNCTION  
PRODUCT  
FOR A4/A3 FORMAT

# FULL FUNCTIONALITY DEPENDABLE AND VERSATILE



- Sharp image quality with real 1,200 x 1,200 dpi printing resolution.
- Quick first copy time in just 3.4 seconds and fast warm up time 17 seconds\*.
- Standard 320GB hard disk capacity and 4GB RAM to meet heavy duty tasks without additional hard drive.
- Support A6 original scanning from Document Processor with fast dual scan speed up to 220/220 ipm A4 Mono/Color\*\* to facilitate digitalization of document for easy storage and retrieval.
- Support SRA3 size (320mm x 450mm) & 300g/m2 paper from standard cassette.
- Allow Banner Print and Scan for easy in-house banner production.
- Semi auto self-closing paper cassette.
- Support different types of robust optional Finisher.

\*For TASKalfa 6003i

\*\* When using optional Document Processor DP-7130



			Main Specifications	
Model			TASKalfa 5003i	TASKalfa 6003i
Main Function			Copy, Print, Scan, Fax (Optional)	
Writing Method			Semiconductor Laser	
CPU			T1024 (Dual Core) 1.2GHz	
Print Speed (A4) (Mono)			50 cpm	60 cpm
Scanning Speed (A4) 300dpi	DP-7100 (Mono/Color)	Simplex	80/80 ipm	
		Duplex	48/48 ipm	
Scanning Speed (A4) 300dpi Dual Scan	DP-7110 (Mono/Color)	Simplex	100/100 ipm	
		Duplex	180/180 ipm	
Scanning Speed (A4) 300dpi Dual Scan with Double Feed Detector	DP-7130 (Mono/Color)	Simplex	120/120 ipm	
		Duplex	220/220 ipm	
Memory			Standard 4GB (Max. 4GB)	
SSD/HDD Capacity			SSD 8GB (Standard) / HDD 320GB (Standard)	
HDD Data Security Kit			Data Security Kit(F)	
Warm Up Time			17 seconds	
Paper Capacity			2 x 500 sheets (Cassette) + 150 sheets (MPT)	
Paper Size	Standard	7,150 sheets (Main Unit + 2 x 1,500 sheets PF-7110 x1 + 3,000 sheets PF-7120 x1 + MPT)		
	Cassette	Min. A6R – Max. SRA3(320mm x 450mm); Cassette 1 Min. A6R – Max. A4R (Legal)		
	MPT	Min. A6R – Max. SRA3(320mm x 450mm) & Banner Print of 1,220mm		
Paper Weight	Cassette	52 – 300 g/m <sup>2</sup>		
	MPT	52 – 300 g/m <sup>2</sup>		
Duplex Printing			Paper size: A6R – SRA3(320mm x 450mm); Paper weight: 64 - 256 g/m <sup>2</sup>	
Output Capacity			Max. 500 sheets + 100 sheets face-down (with Inner Job Separator)	
Control Panel			10.1 inch Color Touch LCD Panel	
Dimension (W x D x H) (Main Unit)			602mm x 665mm x 790mm	
Weight (Main Unit)			Approx. 83 kg	
Power Consumption (Standard configuration)	Copy/Print Mode	740W		870W
	Stand-by Mode		50W	
	Energy Saver		0.7W	
Noise (ISO7779/ ISO9296)	Copy/Print Mode	71dB(A)		73dB(A)
	Stand-by Mode		35dB(A)	
<b>Copy Functions (Standard)</b>				
Copy Size			Max. A3 (Legal) – Min. A6R	
Resolution			600 x 600 dpi	
First Copy Time (Mono)			3.7 seconds	3.4 seconds
Zoom Ratio	Manual	25% - 400% (1% per Step)		
	Pre-defined	7R5E		
Multiple Copy			1 – 9999	
<b>Print Functions (Standard)</b>				
Resolution			1,200 x 1,200 dpi; 4,800 equivalent x 1,200 dpi level	
PDL			PRESCRIBE, PCL6 (PCL-XL, PCL 5e), KPDL3 (Postscript 3 compatible), XPS, OpenXPS, PDF Direct Print Ver. 1.7	
First Print Out Time (Mono)			4.3 seconds	3.8 seconds
Supported Protocol			TCP/IP, NetBEUI, FTP, Port 9100, LPR, IPP, IPP over SSL/TLS, WSD Print, Apple Bonjour	
Operating System Supported			Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows XP, Windows Vista, Windows 7, Windows 8, Windows 8.1; Apple Macintosh OS X 10.5 or later; Linux	
Interface			USB 2.0 High Speedx1; Ethernet 10BASE-T/100BASE-TX/1000BASE-T; USB Host Interface (USB Host)x4; NFC TAGx1	
USB Memory Printing Format			TIFF, JPEG, PDF, XPS	
Mobile Printing			AirPrint, Mopria, KYOCERA Mobile Print	
<b>Scan Functions (Standard)</b>				
Color Selection			Auto Color (Color/Gray); Auto Color (Color/B&W); Full Color; Grayscale; Black & White	
Resolution			600dpi, 400dpi, 300dpi, 200dpi, 200x400dpi, 200x100dpi	
File Format			TIFF, JPEG, XPS, OpenXPS, PDF (MMR/JPG compression/High-compression PDF), PDF/A, Encrypted PDF, Searchable PDF (Optional)	
Image Type Mode			Text, Photo, Text + Photo, Text (Fine Line)	
Transmission Type			Scan to SMB; Scan to E-mail; Scan to FTP or FTP over SSL; Scan to USB; TWAIN Scan; WSD Scan	
Address Storage			2,000 addresses (Common address list), 500 groups (Group address list)	
<b>Fax Functions (Optional)</b>				
Original Size			Max. A3 (Legal) – Min. A6 (statement), Banner: 1,600 (A4)	
Coding Method			MMR, MR, MH, JBIG	
Transmission Speed			33.6 kbps	
Memory			12MB	
DUAL FAX / Network FAX			Yes	
<b>Consumables &amp; Options</b>				
Toner Kit			TK-6329: 35,000 pages	
Maintenance Kit			MK-6335: 600,000 pages	
Document Processor			DP-7100: 140 sheets Reversing Type; DP-7110: 270 sheets One-path duplex scanning Type; DP-7130: 270 sheets One-path Duplex Scanning Type with double paper feed detector	
Paper Feeder			PF-7100: 500 sheets x2; PF-7110: 1,500 sheets x2 (A4/Letter); PF-7120: 3,000 sheets large capacity side deck (A4/Letter)	
Finisher			DF-7100: 500 sheets Inner Finisher; AK-7110: Attachment Kit; DF-7120: 1,000 sheets Finisher; DF-7110: 4,000 sheets Finisher; DF-7130: 4,000 sheets Finisher with 100 sheets Staple PH-7C: Punch Unit for DF-7110/ DF-7120/DF-7130; PH-7120: Punch Unit for DF-7100; MT-730(B): 7 Bin Mailbox Sorter for DF-7110/ DF-7130; JS-7100: 100 sheets Inner Job Separator; BF-730: Booklet Folder for DF-7110; BF-9100: Booklet Folder for DF-7130; SH-10: Staple for DF-7100/DF-7120/BF-730; SH-12: Staple for DF-7110; SH-14: Staple for DF-7130	
Fax System			Fax System 12	
Internet FAX			Internet FAX Kit(A)	
Card Authentication			Card Authentication Kit(B) AC	
Gigabit Ethernet Board			IB-50	
Wireless LAN Interface			IB-35 (802.11 b/g/n/Wireless LAN/WiFi Direct)	
Embedded OCR			Scan Extension Kit(A)	
Banner Paper Feeding Guide			Banner Guide 10	
Numeric Key Pad			NK-7120	
Document Tray			DT-730(B)	
Keyboard Holder			Keyboard Holder 10	



KYOCERA Document Solutions Asia Limited  
13/F, Mita Centre, 552-566 Castle Peak Road, Tsuen Wan, N.T., Hong Kong  
Tel: +852-2496-5678 Fax: +852-2610-2063  
www.kyoceradocumentsolutions.asia

KYOCERA Business Partner

\*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.